

SPC FLOORING FOR NEXT GENERATION





SPC88003-1



SPC88003-3



SPC88004-2



SPC88004-5



SPC88004-2



SPC88004-6



SPC88004-4



SPC88007-1

SPC FLOORING FOR NEXT GENERATION

PLANK SIZE : 7.25" X 48"
WEAR LAYER : 0.3 MM
APPROX WEIGHT: 0.800 KG PER SQ. FT

- 100% WATER PROOF
- FIRE RETRIED
- ANTI STARCH
- ANTI SLIPPERY



SPC88022-6



SPC88023-3



SPC88023-5



SPC88025-5



SPC88026-1



SPC88026-6



SPC99001-4





SPC88007-3



SPC88008-1



SPC88009-1



SPC88009-4



SPC88021-1



SPC88021-6



SPC88022-2



SPC88022-3

Advantage of Polyleaf SPC Flooring:

1) Waterproof and Dampproof

As the main component of SPC is stone power, so it performs well with water, and mildew will not happen with high humidity.

2) Fire Retardant

According to the authorities, 95% of the victims were burned in the fire caused by the toxic fumes and gases. The fire rating of SPC flooring is NFPA CLASS B. Flame retardant, not spontaneous combustion, leave the flame automatic out in 5 seconds, won't produce toxic or harmful gases.

3) No Formaldehyde

Polyleaf SPC is high quality stone powder & PVC resin, without harmful material such as benzene, formaldehyde, heavy metal.

4) No Heavy Metal, No Lead Salt

The Stabilizer of Polyleaf SPC is Calcium zinc, no lead salt heavy metal

5) dimensionally Stable

Exposed to 80° heat, 6 hours—Shrinkage ≤ 0.1%; Curling ≤ 0.2mm

6) High Abrasion

Polyleaf SPC flooring has a transparent wear-resisting layer, whose revolution is up and higher than 10000 turns.

7) Superfine Anti-slipping

Polyleaf SPC flooring has special skid resistance and wear-resisting layer of the floor. Compared with common floor, SPC flooring has higher friction when it's wet.

8) Low requirement of subfloor

Compared to traditional LVT, SPC flooring has a distinct advantage because it is rigid core, which can hide many imperfections of subfloor.

	100% RECYCLABLE		IMPACT RESISTANCE Thick wear layer providing lasting quality
	EASY CLEAN+STAIN RESISTANCE Anti-spill & easy to remove existing stain		ACOUSTIC FRIENDLY Reduce sound by more than 50%
	UV COATED Colour does not fade under sunlight		QUICK, FIT EASY CLICK DESIGN Easy to install on flat surface or tiles
	ANTI-SLIP Slip resistance		SCRATCH+WEAR RESISTANCE Thick wear layer with double UV coating
	NON-TOXIC+ODOURLESS No smell & not hazardous to health		FIRE RESISTANCE B1 Level : Hard to burn
	WATERPROOF highly resistance to water & moisture		ELECTRIC CURRENT RESISTANCE Does not conduct electricity
	INSECT PROOF Insect free due to composition of material		100% FORMALDEHYDE FREE Free from toxic chemical and toxic gas





Flooring Specifications

Plank Size	7.25" x 48", 12" x 24"
Thickness – Wear Layer	4.0mm – 0.3/0.5 & 5.0mm – 0.3/0.5
PVC Grade	100% Virgin
UV Coating	2 layer
Printed film layer	0.07
Installation Type	Click Lock
Acoustic Backing	No Backing / EVA / IXPE
Fire Retardant Rating	B1 Grade
Minimum Order Quantity	1*20'GP FCL Container
Per box	10 Planks
Per Box wt.	20 kg Approx
Product Origin	INDIA

Benefits of Buying SPC Rigid Core From Us

VIRGIN PVC FOR EACH PLANK



Please feel free to contact us..

Hitesh Joshi - Sales & Marketing

call # 9725211327 | whatsapp# 9870269090 | email : polyleaf.spc@gmail.com

SPC FLOORING FOR NEXT GENERATION



305-332-6108



Lagaresfloorinstallation@gmail.com



Lagaresfloorinstallation

